


Silicon PNP transistor in a SOT-23 Plastic Package.

Large Ic low Vce(sat),complementary pair with the 2SC2411K.


Medium power amplifier applications.




PIN1 Base PIN 2 Emitter PIN 3 Collector

h _{FE} Classifications Symbol	P	Q	R
h _{FE} Range	82 180	120 270	180 390
Marking	HHP	HHQ	HHR

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-40	V
Collector to Emitter Voltage	V_{CEO}	-32	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current	I_C	-500	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}		





h_{FE}


Note:

H: Company Code

H: Product Type Code

P: h_{FE} Classifications Symbol Code

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;

2

245 5

5 0.5sec;

3

2 10 /sec.
- 1.Preheating:25~150 , Time:60~90sec.

2.Peak Temp.:245 5 , Duration:5 0.5sec.

3. Cooling Speed: 2~10 /sec.

260 5

10 1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOT-23	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205