

/ Descriptions

TO-92LM PNP Silicon PNP transistor in a TO-92LM Plastic Package.


/ Features

High breakdown voltage, small reverse transfer capacitance and excellent high frequency characteristic.

/ Applications

Color TV chroma output and high breakdown voltage driver.

/ Equivalent Circuit



/ Pinning






PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	C	D	E	F
h_{FE} Range	40~80	60~120	100~200	160~320

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-300	V
Collector to Emitter Voltage	V_{CEO}	-300	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current - Continuous	I_C	-100	mA
Collector Current – Continuous(Pulse)	I_{CP}	200	mA


/ Electrical Characteristic Curve




/ Package Dimensions


TO-92LM

Unit: mm





() / Temperature Profile for Dip Soldering(Pb-Free)



- Note:

1

25 150

60 90sec;

2

255±5

5±0.5sec;

3

2 10 /sec.
- 1.Preheating:25~150 , Time:60~90sec.

2.Peak Temp.:255±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Tf0.56D935.8(5(.7150))TJ/TT7 1 Tf314.9486 0