

描述 / Descriptions

TO-92 NPN Silicon NPN transistor in a TO-92 Plastic Package.


特点 / Features

Small reverse transfer capacitance, low noise figure.

应用 / Applications

High frequency amplifier, FM,RF,MIX IF amplifier applications.

等效电路 / Equivalent Circuit



封装 / Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

hFE 分类及标记 / hFE Classifications & Marking

h _{FE} Classifications Symbol	R	O	Y
h _{FE} Range	40~80	70~140	100~200

Parameter

Symbol

« È Ò Ì f


2SC2668

Rev.E Mar.-2016




DATA SHEET

8 Tc 0 Tw (2w [51http:/ /TT50940.2(kingMar)2breIn)5(struactions/TT2 1 Tf 10.5 0-69 771 --4(657Tc 0 Tw (5)Tj /T 0.



↓ § ¶ ŵ'É Ÿ f (ŦŦŦ) / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

↓ Ŧ Ŧ Ŧ Ŧ Ŧ / Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp:270±5 Time:10±1 sec

Ŧ Ŧ Ŧ Ŧ / Packaging SPEC.

/ BULK

Package Type	Units					Dimension (unit mm3)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-92	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195
	1,000	10	10,000	10	100,000	135×190	237×172×102	560×245×375

/ AMMO

Package Type	Units					Dimension (unit mm3)	
	Units/tape /	Tape/Inner Box /	Rows/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Inner Box	Outer Box
TO-92	3,000	1	120	10	30,000	328×230×42	480×346×235 547×407×268

ä ŵ ŦŦŦ / Notices