2SC3356

Rev.F Apr.-2017

蓝箭电子 BLUE ROCKET ELECTRONICS

DATA SHEET

/ Descriptions

VRW056 ṂṂ Ḫ QSQ ÆṀ ч s ‖ ㄱ Silicon NPN transistor in a SOT-23 Plastic Package.

/ Features

Ӈ ƍ ϕ ⊐ ᵪ ı ' ɯ `

Low noise and high power gain.

/ Applications

ᵮ ת ᵪ ḻ ʌ ᵪ ḻ ⊐ ѿ ɻ Ɔ ð ḻ ㅓOBJӇ ƍ ϕ ѽ ᶻ

low noise amplifier at VHF, UHF and CATV band applications.

/ Equivalent Circuit



/ Pinning



PIN1 χ Base PIN 2 χ Emitter PIN 3 χ Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	Q	R	S	T
h_{FE} Range	50 100	80 160	125 250	200 330
Marking	HR23	HR24	HR25	HR26

v ˝Ω Parameter	٩ N Symbol	˝Ω Ö Rating	D Ч Unit
Collector to Base Voltage	V_{CBO}	20	V
Collector to Emitter Voltage	V_{CEO}	12	V
Emitter to Base Voltage	V_{EBO}	3.0	V
Collector Current	I_C	100	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

v ˝Ω Parameter	٩ N Symbol	Ш :ˆ Ţ Test Conditions	ω ņ Ö Min	Ɛ ʒ Ö Typ	ω ˠ Ö Max	D Ч Unit
Collector Cut-Off Current	I_{CBO}	V_{CB}=10V I_E=0			1.0	μA

TD 8580

/ Electrical Characteristic Curve







/ Package Dimensions



/ Marking Instructions



ِ ّ χ

K χ ѭ ҳ и Ґђ

U56 χ ѭ ҙ N Ґђ

Note:

K χ Company Code

U56 χ Product Type Code

( ) / Temperature Profile for IR Reflow Soldering(Pb Y