

/ Descriptions

TO-251 NPN Silicon NPN transistor in a TO-251 Plastic Package.


/ Features

$V_{CE(sat)}$, h_{FE}
Low saturation voltage, excellent h_{FE} linearity and high h_{FE} .


/ Applications

3
Output stage of 3 watts audio amplifier, voltage regulator, DC-DC converter and relay driver.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter


/ h_{FE} Classifications & Marking

h_{FE} Classification Symbol	R	Q	P	E
h_{FE} Range	60 120	100 200	160 320	200 400

Parameter	Symbol
-----------	--------



/ Electrical Characteristic Curve




$f_T - I_C$


$C_{ob} - V_{EB}$



/ Package Dimensions



/ Marking Instructions



BR

D882I

R: h_{FE}

Note:


BR: Company Code

D882I: Product Type.

R: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只袋	袋盒	只盒	盒箱	只箱	袋	盒	箱

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	只套管	套管盒	只盒	盒箱	只箱	套管	盒	箱

/ Notices