




Parameter	Symbol	Rating	Unit
Input voltage	V_I	7~35	V
Power Dissipation	P_D	Internally Limited	W
Thermal Resistance Junction-Ambient	$R_{\theta JA}$	105	/W
Thermal Resistance Junction-Case	$R_{\theta JC}$	10	/W
Operating Temperature Range	T_{OPR}	-40 125	
Storage temperature range	T_{stg}	-65 150	

Parameter	Symbol	Test Conditions	Min
-----------	--------	-----------------	-----





BR


78D05A

Note:

BR: Company Code

78D05A: Product Type

****: Lot No. Code, code change with Lot No



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit ㎜ mm³)		
	个	盘	个	盘	个	长	宽	高
TO-252	2,500	2	5,000	6	30,000	13 ×16	360×360×50	380×335×366

/ TUBE

Package Type	Units					Dimension (unit ㎜ mm³)		
	个	盘	个	盘	个	长	宽	高
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

PCB