


SOT-89 Voltage Regulator in a SOT-89 Plastic Package.

100mA,
3-Terminal regulators, output current up to 100 mA, internal thermal overload protection and short-circuit limiting,HF Product.

Voltage Regulator.

/ / Equivalent Circuit or Application Circuit




/ Marking


Parameter	Symbol	Rating	Unit
Input voltage	V_I	-35	V
Output current	I_O	100	mA
Junction Temperature	T_J	150	
Operating Temperature Range	T_{OPR}	-40 125	
Storage temperature range	T_{stg}	-65 150	
Power Dissipation	P_D	500	mW

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Output voltage	V_O	$I_O=40mA$ $T_J=25$	-4.80	-5.2	-5.2	V
		-7.5V V_{in} -20V 5mA I_{out} 100mA	-5.25	-5.25	-5.25	
Line Regulation	REGline	-7.5V V_{in} -20V $I_O=40mA$ $T_J=25$		50	150	mV
Load Regulation	REGload	5mA I_{out} 100mA $T_J=25$		20	60	
		5mA I_{out} 40mA $T_J=25$		10	30	
Bias current	I_Q	$I_{out}=0$ $T_J=25$		3	6	mA
Bias current change	I_Q	-8V V_{in}				


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



H

N05

**

Note:

H: Company Code

N05: Product Type Code

** : Lot No. Code, code change with Lot No.

79L05T