


SOT-23 NPN Silicon NPN transistor in a SOT-23 Plastic Package.

, BC327M
High current, complementary pair with BC327M.


General power amplifier and switching.



PIN1 Base PIN 2 Emitter PIN 3 Collector

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	50	V
Collector to Emitter Voltage	V_{CEO}	45	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	800	mA
Collector Emitter - Continuous	I_E	-800	mA
Collector Power Dissipation	P_C	300	mW
Junction Temperature	T_J	150	
Storage Temperature Range	T_{stg}	-55° 150	


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------



SQT-23

单位: mm





H


6C1

Note:

H: Company Code.

6C1: Product Type Code.

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;

1.Preheating:25~150 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7 ρ ×8	180×120×180	390×385×205