

/ Descriptions

SOT-323 PNP Silicon PNP transistor in a SOT-323 Plastic Package.


/ Features

BC847W
High current, low voltage complementary pair with BC847W,HF Product.


/ Applications

General purpose switching and amplification.

/ Equivalent Circuit



/ Pinning





PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	A	B	C
h_{FE} Range	125 250	220 475	420 800
Marking	H3E	H3F	H3G

/ Electrical Characteristic Curve





() / Temperature Profile for IR Reflow Soldering(Pb-Free)

- Note:
- 1

150 180 60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5 5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices