BCX56

Collector to Emitter Voltage	V_{CEO}	80	V
Emitter to Base Voltage	V_{EBO}	5	V
Collector Current-Continuous	I_C	1	A
Peak Collector Current	I_{CM}	1.5	A
Peak Base Current	I_{BM}	0.2	A
Collector Power Dissipation	$P_C(T_C=25$)	1.3	W
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	I_C=100PA I_E=0	100			V
Collector to Emitter Breakdown Voltage	V_{CEO}	I_C=500PA I_B=0	80			V
Emitter to Base Breakdown Voltage	V					

≠ Ǝ ⁋Ạ´E ∀ ƒ / Electrical Characteristic Curve



ᵘ ĖÒĻ ƒ / Package Dimensions

SOT-89

单位：mm



ł. Ļ"Ω / Marking Instructions



ب ˝ χ

H χ ﻫ ३ и Ґ

BK χ ﻫ ȝ N Ґ

-- χ ﻫ ı ғ ń N Ґ ı ₺ ı ғ ń N Ψ ק

Note:

H: Company Code.

BK: Product Type.

**: Lot No. Code, code change with Lot No.

ѫ ʃ ╕ ẘ ´E ⅵ ʃ (ᾠ ƨ) / Wh p shudwxuh Suriloh iru LU Uhior z Vroghulq j+Se0luhh,



ب ˝ χ

1 Ĺ ♬ □ ẙ 25 Ḱ 150 ɬ ı ˋH ڑ 60 Ḱ 90sec;

2 Š Ө □ ẙ 245 ° 5 ɬ ı ˋH ڑ ˋY ⅄ ѭ 5 ° 0.5sec;

3 ì ˙ ⅵ ˛ ɔ ѡ ẙ ѭ 2 Ḱ 10 ɬ /sec.

Note:

1.Preheating:25~150 ɬ , Time:60~90sec.

2.Peak Temp.:245 ° 5 ɬ , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ɬ /sec.

⅄ ŭ ɋ ˉ ˋY Ţ / Resistance to Soldering Heat Test Conditions

□ ẙ χ 260 ° 5 ɬ ˋH ڑ χ 10 ° 1 sec. Temp.:260±5 Time:10±1 sec

ɒ Ŀ ≮ — / Packaging SPEC.

ɔ ` ɣ Ŀ / REEL

Package Type	Units					Dimension		(unit mm^3)
						ρ		

ä ⅴ ŗ Ѿ / Notices