

/ Descriptions

TO-126F

PNP

Silicon PNP transistor in a TO-126F Plastic Package.

/ Features


BD135

Complement to BD135.

/ Applications

Medium power linear and switching applications.

/ Equivalent Circuit



/ Pinning



PIN1 Emitter

PIN 2 Collector

PIN 3 Base

/ h_{FE} Classifications & Marking



h_{FE} Classifications Symbol	6	10	16
h_{FE} Range	40 100	63 160	100 250

BD136

Rev.E Mar.-2016

DATA SHEET

/ Electrical Characteristic Curve



/ Package Dimensions



BD136

Rev.E Mar.-2016

DATA SHEET

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units		Dimension	(unit mm ³)
	Units/Tube /	Tubes/Inner Box /		