

BR1N4007WQ

Rev.A Sep.-2024




DATA SHEET

1000V 1A SOD-123FL
Surface Mount General Purpose Silicon Rectifiers Reverse Voltage 1000V Forward Current 1A
SOD-123FL thin package.

, RoHS 2011/65/EU AEC-Q101

Glass Passivated Chip Junction Ideal for automated placement Lead free in comply with EU RoHS
2011/65/EU directives For surface mounted applications, Qualified to AEC-Q101 Standards for High
Reliability, HF Product.

General purpose, Meet the stringent requirements of automotive applications.



Parameter	Symbol	Rating	Unit
		BR1N4007WQ	
Maximum Receverse Voltag0082e	V_{RRM}		

/ Electrical Characteristic Curve

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Reciprocal Peak Forward Surge Current



/ Package Dimensions

SOD-123FL



/ Marking Instructions




S1M

Note:

S1M Product Type Code

**** Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
SOD-123FL	3,000	8	24,000	6	144,000	7 ×8	185×180×105	390×385×205

/ Notices