

/ Descriptions

PDFN5×6 N

N-Channel MOSFET in a PDFN5 6 Plastic Package.

/ Features


AEC-Q101

Low $R_{DS(ON)}$ to minimize conductive loss; low Gate Charge for fast switching; Low Thermal resistance; Qualified to AEC-Q101 Standards for High Reliability; HF Product.


/ Applications

Battery Management, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning



PIN1 2 3 S PIN4 G PIN5 6 7 8 D

/ Marking

See Marking Instructions.

BRCS010N04SZCQ

Rev.A May.-2023

DATA SHEET

BRCS010N04SZCQ

Rev.A May.-2023



蓝箭电子
BLUE ROCKET ELECTRONICS

DATA SHEET


BRCS010N04SZCQ

Rev.A May.-2023

/ Package Dimensions



/ Marking Instructions



BR

Q

010N04S

Note

BR Company Code

Q: Automobile halogen-free product Code

010N04S Product Type

****: Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)

Note:

- 1

150 200

60 120sec;

1.Preheating:150~200 , Time:60~120sec.
- 2

255±5

5±0.5sec;

2.Peak Temp.:255±5 , Duration:5±0.5sec.
- 3

2 10

/sec.

3. Cooling Speed: 2~10 /sec.