

5 é

TO-220 .> // x P ?ú 3 « | • 'ož

P-CHANNEL MOSFET in a TO-220 Plastic Package.



$V_{DS} = -30V$ $I_D = -98A$

$R_{DS(on)} @ -10V$ "7.0m (Type.6.7m)

$R_{DS(on)} @ -4.5V$ "15m (Type.9.0m)

ä È • ¼ y c 5 ... vo• (3 9o• Ñož

High frequency switching and synchronous rectification,BMS,Motor.



PIN1 y G PIN 2o•4 y D PIN 3 y S

, M V

• - ~ a ¢ož




See Marking Instructions.

@ f Parameter	... Z Symbol	$f >$ Rating	% y Unit
Drain-Source Voltage	V_{DS}	-30	V
Drain Current - Continuous	$I_D(T_c=25^\circ\text{C})$	-98	A
Drain Current – Pulsed	I		

④ì × ? d ;

@ f Parameter	... Z Symbol	y ì Ú ^ Test Conditions	Â 4 > Min	Á ° > Typ	Â Ý > Max	% y Unit
Turn-On Delay Time	t _{d(on)}	V _{GS} =-10V V _{DS} =-15V R _L =0.75 ì R _{GEN} =3 ì		12.5		ns
Turn-On Rise Time	t _r			19		
Turn-Off Delay Time	t _{d(off)}			125		
Turn-Off Fall Time	t _f			67		


Ô ? d • Ž ¢



Ø □ =) ☉



, M y f



^a ϕ y
(8 y , [W A
6 y ° Z W A
y ŷ D Z W A k š ŷ D Z J

Note:
BR: Company Code
070P03: Product Type Code
****: Lot No. Code, code change with Lot No

G PD t ... • Ž Ć x /

^a Ć y

- 1o• Ä ½ “† 25 ½150 - k ž • 60 ½90sec;
- 2o• Q > “† 255 r5 - k ž • 4 Ò 5 r0.5sec;
- 3o•D N ò i Ò 0 ,† 2 ½10 - /sec.

Note:

- 1.Preheating:25~150 - , Time:60~90sec.
- 2.Peak Temp.:255 r5 - , Duration:5 r0.5sec.
3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »]

“† y 270 r5 - ž • y 10 r