

Rev.A Dec.-2022

PDFN 3×3A-8L P MOS

P-Channel Enhancement Mode Field Effect Transistor in a PDFN 3×3A-8L Plastic Package.

$V_{DS} (V) = -40V$



$I_D = -41A (V_{GS} = \pm 20V)$

$R_{DS(ON)} @ -10V \leq 13.5mR (Typ. 11.6mR)$

HF Product.

/

Notebook AC-in load switch, Battery protection charge/discharge.






出脚	定义
Pin1	S
Pin2	S
Pin3	S
Pin4	S
Pin5	S
Pin6	S
Pin7	S
Pin8	S

See Marking Instructions.


Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DS}	-40	V
Drain Current - Continuous		$I_D(T_c=25^\circ\text{C})$	-41	A
Drain Current – Pulsed		I_{DM}	-72	A
Gate-Source Voltage		V_{GS}	± 20	V
Power Dissipation		$P_D(T_c=25^\circ\text{C})$	30	W
Single Pulse Avalanche Energy(L=0.5mH)		E_{AS}	317.5	mJ
Avalanche Current(L=0.5mH)		I_{AS}	-31.5	A
Junction and Storage Temperature Range		T_j, T_{stg}	-55 to 150	
Thermal resistance, junction - ambient	$t \leq 10s$	$R_{\theta JA}$	22	/ W
	Steady-State		55	
Thermal resistance, junction - case				

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=-10V$ $V_{DS}=-20V$ $R_L=0.75\Omega$ $R_{GEN}=3\Omega$		11		ns
Turn-On Rise Time	t_r			7.8		
Turn-Off Delay Time	$t_{d(off)}$			44		
Turn-Off Fall Time	t_f			18		




PDFN3X3A-8L

Unit:mm



Dimensions In Millimeterer			
Symbol	MIN	TYP	MAX
A	3.20	3.30	3.40
A1	3.10	3.15	3.20
B	3.20	3.30	3.40
B1	2.95	3.00	3.05

Rev.00 202011



BR

120P04

Temperature Profile for IR Reflow Soldering(Pb-Free)

Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec
-------	-----------	-------------	---------------

/ REEL

Package Type	Units					Dimension (unit: mm ³)		
	Units/Reel 个/盘	Reels/Inner Box 盘/箱	Units/Inner Box 个/箱	Inner Boxes/Outer Box 箱/箱	Units/Outer Box 个/箱	Reel	Inner Box	Outer Box

PDFN 3