

Rev.A Nov.-2023

: 5 .> // x 4 6 4 ! - } â 'ož

Silicon 4 6 4transistor in a TO-252 Plastic Package.

(8 3 0 * * 6 ; m k —)í D }ož

@ f Parameter	... Z Symbol	f > Rating	% y Unit
Collector to Base Voltage	V _{CBO}	80	V
Collector to Emitter Voltage	V _{CEO}	80	V
Emitter to Base Voltage	V _{EBO}	5.0	V
Collector Current - Continuous	I _C	8.0	A
Collector Peak Current	I _{CM}	16.0	A
Collector Power Dissipation	P _D (T _A =25 -)	1.75	W
Collector Power Dissipation	P _D (T _C =25 -)	20	W
Junction Temperature	T _j	150	
Storage Temperature Range	T _{stg}	-55 150	

@ f Parameter	... Z Symbol	y i Ú ^ Test Conditions	Â 4 > Min	Á ° > Typ	Â Ý > Max	% y Unit
Collector to Emitter Breakdown Voltage						
Collector Cut-Off Current	I _{CES}	V _{CE} = 80V V _{BE} = 0				

Ω ? d • Ž ¢






Figure 1. DC Current Gain

Figure 2. DC Current Gain



$$\emptyset \cap =) \mathbb{C}$$


单位: mm

Symbol		Symbol	
Max	Min	Max	Min
6.25	2.20	2.40	5.95
0.50	0.90	0.43	4.73
1.61	0.45	1.1	9.45
0.60	0.69	6.45	6.25
5.10	5.50	0.00	0.00

FD-302a (Rev. 11-29-70)

BR y , [W A
3 0 * y ° Z W A
y ŷ D Z W A k š ŷ D Z J

BR:	Company Code
MJD44:	Product Type Code
****:	Lot No. Code, code change with Lot No

Rev.A Nov.-2023