/ Descriptions

SOD-123FL

Silicon Bidirectional Trigger Diodes SOD-123FL thin package

/ Features

Use in thyristor phase control,circuits for lamp-dimming,universal-motor speed controls,and heat controls.Halogen free product

/ Applications

.

General purpose.


/ Equivalent Circuit



/ Pinning



PIN	DESCRIPTION
1	Cathode
2	Anode




/ Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit
Power Dissipation T_C=100	P_{tot}	150	mW
Repetitive Peak On-state Current tp=20us f=100Hz	I_{TRM}	2	A
Operating Junction and Storage Temperature Range	T_j T_{stg}	-40 to +125	


Parameter	Symbol	Test Conditions		Min	Max	Unit
Breakover Voltage	V_{BO}	C=22nF see diagram 1	DB3W	28	36	V
			DC34W	30	38	V

/ Package Dimensions



/ Marking Instructions

Marking



/ Marking Instructions



DB3W


**** 1 3

Note:

DB3W Product Type Code

**** Lot No. Code The 1st "*" means:YM Code The last 3 "*" means:little Lot No Code

( ) /



Note:

1 25 150 60 90sec;

1.Preheating:25~150 , Time:60~90sec.

2 245±5 5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3 2 10 /sec.

3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOD-123FL	3000	8	24000	5	120000	7 ×11	185X180X105	390X385X205

/ Notices