

/ Descriptions


SOT-23

NPN

Silicon NPN transistor in a SOT-23 Plastic Package.

/ FeaturesHigh G_{pe} .**/ Applications**

HF,VHF band amplifier application.

/ Equivalent Circuit**/ Pinning**

PIN 1 Base

PIN 2 Emitter



PIN 3 Collector

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	R	O	Y
h_{FE} Range	40 80	70 140	120 240
Marking	HRR	HRO	HR Y


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	35	V
Collector to Emitter Voltage	V_{CEO}	30	V
Emitter to Base Voltage	V_{EBO}	4.0	V
Collector Current	I_C	50	mA
peratCurgrge			50

/ Electrical Characteristic Curve



SUT-23

单位: 湖南大学



/ Marking Instructions



H

R

R h_{FE}

Note:


H Company Code

R Product Type

R h_{FE} Classifications Symbol



() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
SOT-23	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205