


/ Descriptions

TO-220F


/ Features

/ Applications

/ Equivalent Circuit



/ Pinning



/ h_{FE} Classifications & Marking

/ Absolute Maximum Ratings(Ta=25)

	θ		

/ Electrical Characteristics(Ta=25)

/ Electrical Characteristic Curve







FIG. 3-TYPICAL REVERSE CHARACTERISTICS

FIG. 4-TYPICAL FORWARD CHARACTERISTICS


FIG.



/ Package Dimensions



/ Marking Instructions



BR

MBRF1060

CT:

$\pm$ $\pm$

封装形式	包装数量					包装尺寸		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

封装形式 TO-220/F	包装数量					包装尺寸 :		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱