

5 é / Descriptions

: 5 , .> // x RK Ô Â 8 â 'ož

Schottky Barrier Diode in a TO-220F Plastic Package.

□^a / Features

z ô C â k ä | ä g ož

Low poer losses, High efficiency operation.

Đ ÷ / Applications

9 ä È ä " J ~ k • ¼ > k Ò v 8 â ' k 5 8 O T M 8 â ' k *) *) ô E ~ y P F g ' ož

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

Ã W] Ô · / Equivalent Circuit

• Ũ - æ / Pinning

PIN1 y Anode PIN 2 y Cathode PIN 3 y Anode

, M V / Marking

• - ~^a ¢ ož

See Marking Instructions.

Electrical Characteristics(Ta=25℃ ;)

@ f Parameter	... Z Symbol	f > Rating						% y Unit
		MBRFXCT						
		2040	2045	2060	20100	20150	20200	
PeakRepetitive Reverse Voltage	V _{RM}	40	45	60	100	150	200	V
RMS Reverse Voltage	V _{RMS}	28	32	42	70	105	140	V
DC Blocking Voltage	V _{DC}	40	45	60	100	150	200	V
Average Rectified Forward Current	I _{F(AV)}	10X2						A
Forward Voltage at 10A	V _F	0.70		0.75	0.85	0.90	0.92	V
Instantaneous Ta=25 ρ Reverse Current Ta=125 ρ	I _R	0.1			0.05			mA
		20			20			
Typical Junction (1) Capacitance	C _J	600		400				pF
Non Repetitive Peak Surge Current	I _{FSM}	150						A
Thermal Resistance (2) Junction to Case	R _{JA}	45						ρ/W
Junction and Storage Temperature Range	T _j T _{stg}	-55~150				-55~175		ρ

Notes

(1) Measured at 1 MHz and applied reverse voltage of 4 V D.C

(2) P.C.B. mounted with 10cmX10cmX1mm copper pad areas.

Ø α =) ¢ / Package Dimensions

MBRF2040CT~MBRF20200CT

Rev.A29aTf ()220.1(N)224.3(o)225(v)295.6(.)220.1(-)221.9(2)225(0)218.3(2)225(4)225(

