

	!"#\$%				
&	!'"\$(\$!				

) ! "\$"!\$ # (

/ Descriptions

SOT-363 塑封封装双 NPN 半导体三极管。

Double silicon NPN transistor in a SOT-363 Plastic Package.

/ Features



低电压，低电流。无卤产品。

Low current, Low voltage。HF Product.

/ Applications

用于普通放大及开关。

General purpose amplifier and switching.



PIN 1、 4 : Emitter

PIN 2、 5 : Base

PIN 3、 6 : Collector

/ h_{FE} Classifications & Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	40	V
Emitter to Base Voltage	V_{EBO}	6.0	V
Collector Current	I_C	200	mA
Collector Power Dissipation	P_C	200	mW
	$*P_C$	350	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	-55 150	°C

*When mounted on a 7×5×0.6mm ceramic board

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C=10\mu A$ $I_E=0$	60			V
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=1.0mA$ $I_B=0$	40			V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E=10\mu A$ $I_C=0$	6.0			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=30V$ $I_E=0$			0.05	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=3.0V$ $I_C=0$			0.05	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=1.0V$ $I_C=10mA$	100		300	
	$h_{FE(2)}$	$V_{CE}=1.0V$ $I_C=100mA$	30			
	$h_{FE(3)}$	$V_{CE}=1.0V$ $I_C=50mA$	60			
	$h_{FE(4)}$	$V_{CE}=1.0V$ $I_C=1.0mA$	70			
	$h_{FE(5)}$	$V_{CE}=1.0V$ $I_C=0.1mA$	40			
Collector-Emitter Saturation Voltage	$V_{CE(sat)(1)}$	$I_C=10mA$ $I_B=1.0mA$			0.2	V
	$V_{CE(sat)(2)}$	$I_C=50mA$ $I_B=5.0mA$			0.3	V
Base-Emitter Saturation Voltage	$V_{BE(sat)(1)}$	$I_C=10mA$ $I_B=1.0mA$	0.65		0.85	V

/ Marking Instructions

M A *
* *

● “ ”

Note:

●

Product Type Code

Lot No. Code, code change with Lot No.

M
Re



DATA SHEET

Reflow Soldering Temperature Profile for IR Reflow Soldering(Pb-Free)

- 1

60

90sec;

Note:
1.Preheating:150~180°C, Time:60~90sec.
- 2

5±0.5sec;

2.Peak Temp.:245±5°C, Duration:5±0.5sec.
- 3

10°C/sec.

3. Cooling Speed: 2~10°C/sec.

Resistance to Soldering Heat Test Conditions

260 10±1 sec. Temp.:260±5°C Time:10±1 sec

Reflow Soldering SPC

EEL

Package Type 封装形式	Units/Reel	Reels/Box	Units 包装数量	Units/Outer Box
SOT-363	3,000			