/ Descriptions

TO-277

TO-277 Plastic package Ultrafast Recovery Diode.

/ Features

Silicon epitaxial process to produce ultrafast recovery diode with low reverse leakage current and high reliability. HF Product.

/ Applications

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.

/ Equivalent Circuit



/ Pinning



PIN1 Anode PIN 2 Cathode PIN 3 Anode



Suggested Pad layout

/ h_{FE} Classifications & Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	600	V
RMS Reverse voltage	V_{RMS}	420	V
Average Rectified Forward Current	I_F	8	A
Non-Repetitive Peak Forward Surge Current	I_{FSM}	125	A
Thermal Resistance Junction to Case	R_{Jc}	3.5	/W
Junction and Storage Temperature Range	T_j T_{stg}	-55 150	

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Reverse Voltage	V_{BR}	I_R=100uA		600			V
Forward voltage	V_F	I_F=8A	Tc=25		1.4	1.7	V
		I_F=16A	Tc=25		1.7	2.1	V
		I_F=8A	Tc=125		1.4	1.7	V
Instantaneous Reverse Current	I_R Note 1	V_R=600V	Ta=25			5	uA
		V_R=480V	Ta=125			300	uA
		V_R=600V	Ta=125			500	uA

/ Electrical Characteristic Curve







/ Package Dimensions



/ Marking Instructions



MUR860
****

Note:

MUR860	Product Type.
****:	Lot No. Code, code change with Lot No.