


SOT-323 PNP Silicon PNP transistor in a SOT-323 Plastic Package.

S8050W
Complementary pair with S8050W.

Power amplifier applications.

等效电路 / Equivalent Circuit




PIN1 Emitter PIN 2 Base PIN 3 Collector

封装 / MT4 170.5 57344 1bg.9 55D2.8(2)h4.4(e)2g

Parameter	Symbol	Rating	Unit
-----------	--------	--------	------

Electrical Characteristic Curve




⌘ È Ò Ì f / Package Dimensions

SOT-323

单位: mm



1. 1.1 / Marking Instructions



H

Y4

B h_{FE}


Note:

H: Company Code.

Y4: Product Type.

B h_{FE} Classifications Symbol

Whp shudwxuh Suriloh i ru LU Uhior z Vroghulq j+Se0l uhh,



Note:

- 1. Preheating: 25~150 , Time: 60~90sec.
- 2. Peak Temp.: 245±5 , Duration: 5±0.5sec.
- 3. Cooling Speed: 2~10 /sec.

Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.: 260±5 Time: 10±1 sec

Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

Notices /