/ Descriptions

Surface Mount Schottky Barrier Rectifier, Reverse Voltage 45 V, Forward Current 5.0A,SMAF thin package.

/ Features

Low power loss, high efficiency, High forward surge current capability, For use in low voltage, high frequency inverters, and polarity protection applications, For surface mounted applications. Halogen free product.

/ Applications

General purpose.

/ Equivalent Circuit

/ Pinning

PIN	DESCRIPTION
1	Cathode
2	Anode



/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

v Ω Parameter	ʏ N Symbol	Ω Θ Rating	D Ꮒ Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	45	V
Maximum RMS voltage	V_{RMS}	32	V
Maximum DC Blocking Voltage	V_{DC}	45	V
Maximum Average Forward Rectified Current	$I_{F\ AV}$	5.0	A
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	150	A
Typical Junction Capacitance[1)]	C_j	400	pF
Typical Thermal Resistance[2)]	$R_{\ JA}$	60	/W
Operating Junction Temperature Range	T_j	-55~+150	
Storage Temperature Range	T_{stg}	-55~+150	

Note:

1 ζ Measured at 1MHz and applied reverse voltage of 4V D.C

2 ζ P.C.B. mounted with 2.0 X2.0" (5 X 5 cm) copper pad areas.

/ Electrical Characteristics(Ta=25)

v Ω Parameter	ʏ N Symbol	Ⅱ : ⎍ Ꮖ Test Conditions	Rating	D Ꮒ Unit
Max Instantaneous Forward Voltage	V_F	I_F=5.0A	0.55	V
Maximum DC Reverse Current at Rated DC Reverse Voltage	I_R	T_j=25	1	mA
		T_j=100	50	

/ Electrical Characteristic Curve



4

/ Marking Instructions

Marking

/ Marking Instructions

( ) /