

TIP32

Rev. H Oct.-2018

/ Descriptions

WR0553 ММ Ё SQS æ Ć ģ s ll 1 Silicon PNP transistor in a TO-220 Plastic Package.


/ Features

лЪ WLS64 Ы ´
Complement to TIP31.


/ Applications

Ѓ Ć Ć А І ' ħ Ó Æ Ĥ Ŵ º
Medium power linear switching applications.

/ Equivalent Circuit



/ Pinning



PIN1 χ Base PIN 2 χ Collector PIN 3 χ Emitter

/ h_{FE} Classifications & Marking

ø м ђ б " See Marking Instructions.

TIP32

Rev. H Oct.-2018







蓝箭电子
BLUE ROCKET ELECTRONICS

DATA SHEET

Parameter	Symbol	Rating				Unit
		TIP32	TIP32A	TIP32B	TIP32C	
Collector to Base Voltage	V_{CBO}	-40	-60	-80	-100	V
Collector to Emitter Voltage	V_{CEO}	-40	-60	-80	-100	V
Emitter to Base Voltage	V_{EBO}	-5.0				V
Collector Current-Continuous	I_C	-3.0				A
Peak Collector Current	I_{CP}	-5.0				A
Base Current - Continuous	I_B	-3.0				A
Collector Power Dissipation	P_C	2.0				W
Collector Power Dissipation	$P_C (T_c=25^\circ C)$	40				W
Junction Temperature	T_j	150				
Storage Temperature Range	T_{sag}	-55 150				

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



б " X

EU X

WLS65 X

---- X

Note:

BR:

TIP32:

****:

м з " Пб

м ф β з N

м т ф њ N Пб т ф њ N ψ ρ

Company Code

Product Type.

Lot No. Code, code change with Lot No.

